


|              |   |                  |                     |
|--------------|---|------------------|---------------------|
| Manufacturer |  | Type testing No. | EAPR-GS-7516/12     |
|              |   | Location         | Malcesine, Gardasee |
| Model        | Prion2 XS   | Bad Grönenbach:  | 04.06.12            |



EAPR e.V - Marktstr. 11 - D-87730 Bad Grönenbach - Germany

|                         |                                     |   |                                     |   |
|-------------------------|-------------------------------------|---|-------------------------------------|---|
| Date of testing         | Minimum take off weight<br>25.05.12 |   | Maximum take off weight<br>15.04.12 |   |
| Testpilot               | Daniela Martin                      |  | Hannes Tschofen                     |  |
| Harness                 | Academy Test Equipment              |   | Academy Test Equipment              |   |
| Pilot's take off weight | 70 kg                               |   | 90 kg                               |   |

|                |   |
|----------------|---|
| Classification | A |
|----------------|---|



| Test-criteria  | 41054                            | Evaluation | 41014                            | Evaluation |
|--|----------------------------------|------------|----------------------------------|------------|
| <b>1. Inflation / take-off - 4.1.1</b>   |                                  |            |                                  |            |
| Rising behavior  | Smooth, easy and constant rising | A          | Smooth, easy and constant rising | A          |
| Special take off technique required  | No                               | A          | No                               | A          |
| <b>2. Landing - 4.1.2</b>  |                                  |            |                                  |            |
| Special landing technique required   | No                               | A          | No                               | A          |
| <b>3. Speeds in straight flight - 4.1.3</b>                                    |                                  |            |                                  |            |
| Trim speed more than 30km/h  | Yes                              | A          | Yes                              | A          |
| Speed range using the controls larger than 10km/h                              | Yes                              | A          | Yes                              | A          |
| Minimum speed  | Less than 25 km/h                | A          | Less than 25 km/h                | A          |
| <b>4. Control movement - 4.1.4</b>   |                                  |            |                                  |            |
| Max. weight in flight up to 80kg   | Increasing > 55cm                | A          |                                  | -          |
| Max. weight in flight 80 to 100kg  |                                  | -          | Increasing > 60cm                | A          |
| Max. weight in flight greater than 100kg                                       |                                  | -          |                                  | -          |
| <b>5. Pitch stability exiting accelerated flight - 4.1.5</b>                   |                                  |            |                                  |            |
| Dive forward angle on exit   | Dive forward less than 30°       | A          | Dive forward less than 30°       | A          |
| Collapse occurs  | No                               | A          | No                               | A          |
| <b>6. Pitch stability operating controls during accelerated flight - 4.1.6</b> |                                  |            |                                  |            |
| Collapse occurs  | No                               | A          | No                               | A          |
| <b>7. Roll stability and damping - 4.1.7</b>                                   |                                  |            |                                  |            |
| Oscillations   | Reducing                         | A          | Reducing                         | A          |
| <b>8. Stability in gentle spirals - 4.1.8</b>                                  |                                  |            |                                  |            |
| Tendency to return to straight flight  | Spontaneous exit                 | A          | Spontaneous exit                 | A          |
| <b>9. Behaviour in a steeply banked turn - 4.1.9</b>                           |                                  |            |                                  |            |
| Sink rate after two turns  | 12m/s to 14m/s                   | A          | 12m/s to 14m/s                   | A          |
| <b>10. Symmetric front collapse - 4.1.10</b>                                   |                                  |            |                                  |            |
| Entry  | Rocking back less than 45°       | A          | Rocking back less than 45°       | A          |
| Recovery   | Spontaneous in less than 3 sec   | A          | Spontaneous in less than 3 sec   | A          |
| Dive forward angle on exit   | 0° - 30° Keeping course          | A          | 0° - 30° Keeping course          | A          |
| Cascade occurs   | No                               | A          | No                               | A          |
| Entry  | Rocking back less than 45°       | A          | Rocking back less than 45°       | A          |
| Recovery   | Spontaneous in less than 3 sec   | A          | Spontaneous in less than 3 sec   | A          |
| Dive forward angle on exit   | 0° - 30° Keeping course          | A          | 0° - 30° Keeping course          | A          |
| Cascade occurs   | No                               | A          | No                               | A          |
| <b>11. Exiting deep stall (parachutal stall) - 4.1.11</b>                      |                                  |            |                                  |            |

|  |   |                          |   |           |                          |       |                    |           |   |
|--|---|--------------------------|---|-----------|--------------------------|-------|--------------------|-----------|---|
| Deep stall achieved  | Yes   |                          | Yes   |           |                          |       |                    |           |   |
| Recovery   | Spontaneous in less than 3 sec                | A                        | Spontaneous in less than 3 sec                | A         |                          |       |                    |           |   |
| Dive forward angle on exit   | 0° - 30°                                      | A                        | 0° - 30°                                      | A         |                          |       |                    |           |   |
| Change of course   | Changing course less than 45°                 | A                        | Changing course less than 45°                 | A         |                          |       |                    |           |   |
| Cascade occurs   | No  | A                        | No  | A         |                          |       |                    |           |   |
| <b>12. High angle of attack recovery - 4.1.12</b>                                |   |                          |   |           |                          |       |                    |           |   |
| Recovery   | Spontaneous in less than 3 sec                | A                        | Spontaneous in less than 3 sec                | A         |                          |       |                    |           |   |
| Cascade occurs   | No  | A                        | No  | A         |                          |       |                    |           |   |
| <b>13. Recovery from a developed full stall - 4.1.13</b>                         |   |                          |   |           |                          |       |                    |           |   |
| Dive forward angle on exit   | 0° - 30°                                      | A                        | 0° - 30°                                      | A         |                          |       |                    |           |   |
| Collapse   | No collapse                                   | A                        | No collapse                                   | A         |                          |       |                    |           |   |
| Cascade occurs (other than collapse)   | No  | A                        | No  | A         |                          |       |                    |           |   |
| Rocking backward   | Less than 45°                                 | A                        | Less than 45°                                 | A         |                          |       |                    |           |   |
| Line tension   | Most lines tight                              | A                        | Most lines tight                              | A         |                          |       |                    |           |   |
| <b>14. Asymmetric collapse (trim speed) - 4.1.14</b>                             |   |                          |   |           |                          |       |                    |           |   |
| Change of course until re-inflation  | trim speed,<br>max 50% collapse               | < 90°                    | Dive or roll angle                            | 0° - 15°  | A                        | < 90° | Dive or roll angle | 0° - 15°  | A |
| Re-inflation behavior  |   | Spontaneous re-inflation |   | A         | Spontaneous re-inflation |       | A                  |           |   |
| Total change of course   |   | Less than 360°           |   | A         | Less than 360°           |       | A                  |           |   |
| Collapse on the opposite side occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Twist occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Cascade occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Change of course until re-inflation  | trim speed,<br>max 75% collapse               | < 90°                    | Dive or roll angle                            | 0° - 15°  | A                        | < 90° | Dive or roll angle | 15° - 45° | A |
| Re-inflation behavior  |   | Spontaneous re-inflation |   | A         | Spontaneous re-inflation |       | A                  |           |   |
| Total change of course   |   | Less than 360°           |   | A         | Less than 360°           |       | A                  |           |   |
| Collapse on the opposite side occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Twist occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Cascade occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Change of course until re-inflation  | accelerated,<br>max 50% collapse              | < 90°                    | Dive or roll angle                            | 15° - 45° | A                        | < 90° | Dive or roll angle | 15° - 45° | A |
| Re-inflation behavior  |   | Spontaneous re-inflation |   | A         | Spontaneous re-inflation |       | A                  |           |   |
| Total change of course   |   | Less than 360°           |   | A         | Less than 360°           |       | A                  |           |   |
| Collapse on the opposite side occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Twist occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Cascade occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Change of course until re-inflation  | accelerated,<br>max 75% collapse              | < 90°                    | Dive or roll angle                            | 15° - 45° | A                        | < 90° | Dive or roll angle | 15° - 45° | A |
| Re-inflation behavior  |   | Spontaneous re-inflation |   | A         | Spontaneous re-inflation |       | A                  |           |   |
| Total change of course   |   | Less than 360°           |   | A         | Less than 360°           |       | A                  |           |   |
| Collapse on the opposite side occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Twist occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| Cascade occurs   |   | No                       |   | A         | No                       |       | A                  |           |   |
| <b>15. Directional control with a maintained asymmetric collapse - 4.1.15</b>    |   |                          |   |           |                          |       |                    |           |   |
| Able to keep course straight   | Yes   | A                        | Yes   | A         |                          |       |                    |           |   |
| 180° turn away from the collapsed side possible in 10 sec                        | Yes   | A                        | Yes   | A         |                          |       |                    |           |   |
| Amount of control range between turn and stall or spin                           | More than 50% of the symmetric control travel | A                        | More than 50% of the symmetric control travel | A         |                          |       |                    |           |   |
| <b>16. Trim speed spin tendency - 4.1.16</b>                                     |   |                          |   |           |                          |       |                    |           |   |
| Spin occurs  | No  | A                        | No  | A         |                          |       |                    |           |   |
| <b>17. Low speed spin tendency - 4.1.17</b>                                      |   |                          |   |           |                          |       |                    |           |   |
| Spin occurs  | No  | A                        | No  | A         |                          |       |                    |           |   |
| <b>18. Recovery from a developed spin - 4.1.18</b>                               |   |                          |   |           |                          |       |                    |           |   |
| Spin rotation angle after release  | Stops spinning in less than 90°               | A                        | Stops spinning in less than 90°               | A         |                          |       |                    |           |   |
| Cascade occurs   | No  | A                        | No  | A         |                          |       |                    |           |   |
| <b>19. B-line-stall - 4.1.19</b>   |   |                          |   |           |                          |       |                    |           |   |
| Change of course before release  | Changing course less than 45°                 | A                        | Changing course less than 45°                 | A         |                          |       |                    |           |   |
| Behaviour before release   | Remains stable with straight span             | A                        | Remains stable with straight span             | A         |                          |       |                    |           |   |
| Recovery   | Spontaneous in less than 3 sec                | A                        | Spontaneous in less than 3 sec                | A         |                          |       |                    |           |   |
| Dive forward angle on exit   | 0° - 30°                                      | A                        | 0° - 30°                                      | A         |                          |       |                    |           |   |
| Cascade occurs   | No  | A                        | No  | A         |                          |       |                    |           |   |
| <b>20. Big ears - 4.1.20</b>   |   |                          |   |           |                          |       |                    |           |   |
| Entry procedure  | Special device required                       | A                        | Special device required                       | A         |                          |       |                    |           |   |
| Behaviour during big ears  | Stable flight                                 | A                        | Stable flight                                 | A         |                          |       |                    |           |   |
| Recovery   | Spontaneous in less than 3 sec                | A                        | Spontaneous in less than 3 sec                | A         |                          |       |                    |           |   |
| Dive forward angle on exit   | 0° - 30°                                      | A                        | 0° bis 30°                                    | A         |                          |       |                    |           |   |
| <b>21. Big Ears in accelerated flight - 4.1.21</b>                               |   |                          |   |           |                          |       |                    |           |   |
| Entry procedure  | Special device required                       | A                        | Special device required                       | A         |                          |       |                    |           |   |
| Behaviour during big ears  | Stable flight                                 | A                        | Stable flight                                 | A         |                          |       |                    |           |   |
| Recovery   | Spontaneous in less than 3 sec                | A                        | Spontaneous in less than 3 sec                | A         |                          |       |                    |           |   |
| Dive forward angle on exit   | 0° - 30°                                      | A                        | 0° bis 30°                                    | A         |                          |       |                    |           |   |
| Behaviour immediately after releasing the accelerator while maintaining big ears | Stable flight                                 | A                        | Stable flight                                 | A         |                          |       |                    |           |   |
| <b>22. Behaviour exiting a steep spiral - 4.1.22</b>                             |   |                          |   |           |                          |       |                    |           |   |

|  |                                      |  |                                      |    |
|--|--------------------------------------|--|--------------------------------------|----|
| Tendency to return to straight flight  | Spontaneous exit                     | A  | Spontaneous exit                     | A  |
| Turn angle to recover normal flight  | Less than 720°, spontaneous recovery | A  | Less than 720°, spontaneous recovery | A  |
| <b>23. Alternative means of directional control - 4.1.23</b>                                       |                                      |  |                                      |    |
| 180° turn achievable in 20 sec   | Yes                                  | A  | Yes                                  | A  |
| Stall or spin occurs   | No                                   | A  | No                                   | A  |
| <b>24. Any other flight procedure and/or configuration described in the user's manual - 4.1.24</b> |                                      |  |                                      |    |
| Procedure works as described   |                                      | NA   |                                      | NA |
| Procedure suitable for novice pilots   |                                      | NA   |                                      | NA |
| Cascade occurs   |                                      | NA   |                                      | NA |
| <b>25. Remarks of testpilot:</b>   |                                      |  |                                      |    |
|  |                                      |  |                                      |    |
|  |                                      |  |                                      |    |
|  |                                      |  |                                      |    |
|  |                                      |  |                                      |    |
| Copyright Ralf Antz 2010   |                                      | This Flight Test Report was generated automatically and is valid without signature |                                      |    |