



DHV-tested Equipment | Flying Equipment Database | Manufacturers / Dealers | Flying Schools | Clubs

DHV Databases

[TECHNICAL DATA](#) [DHV TESTREPORT LTF](#) [DATASHEET](#) [PRINT](#)

DHV TEST REPORT LTF 2003



NOVA RADON S

Type designation Nova Radon S**Type test reference no** DHV GS-01-1183-03**Holder of certification** NOVA Vertriebsgesellschaft m.b.H.**Manufacturer** NOVA Vertriebsgesellschaft m.b.H.**Classification** 2-3 GH**Winch towing** Yes**Number of seats min / max** 1 / 1**Accelerator** Yes**Trimmers** No

| BEHAVIOUR AT MIN WEIGHT IN FLIGHT (70KG) | BEHAVIOUR AT MAX WEIGHT IN FLIGHT (100KG) |
|--|---|
|--|---|

[Take off](#)

|1-2

|1-2

Inflation evenly, immediately

evenly, immediately

Rising behaviour immediately comes over pilot

immediately comes over pilot

Take off speed average

average

Take off handling average

average

[Straight flight](#)

|1-2

|1-2

Roll damping average

average

[Turn handling](#)

|2

|2

Spin tendency average

average

Control travel average

average

Agility average

high

[Symmetric stall](#)

|2

|2

Deep-stall limit average 60 cm - 75 cm

average 60 cm - 75 cm

Full stall limit average 65 cm - 80 cm

average 65 cm - 80 cm

Increase in steering power high

high

[Front collapse](#)

|1-2

|2

Pre-acceleration average

average

Opening behaviour spontaneous, delayed

spontaneous, delayed

[Asymmetric collapse](#)

|2

|2

Turn tendency 180 - 360 degrees

180 - 360 degrees

Change of course 180 - 360 degrees

180 - 360 degrees

Rate of turn average

average

with deceleration

with deceleration

Max. roll/pitch angle greater than 45 degrees

greater than 45 degrees

Loss of altitude average

average

Stabilization spontaneous

spontaneous

Opening behaviour spontaneous, delayed

spontaneous, delayed

[Countersteering an asymmetric collapse](#)

|1-2

|1-2

Stabilization countersteering easy

countersteering easy

Control travel average

average

Control pressure increase high

high

Turn in opposite direction easy, no tendency to stall

easy, no tendency to stall

Opening behaviour spontaneous, delayed

spontaneous, delayed

[Full stall, symm. exit](#)

|1-2

|2

[Spin out of straight flight](#)

|1-2

|1-2

[Spin out of turn](#)

|1-2

|1-2

[Spiral dive](#)

|2

|2

Entry average

average

Spin tendency slight

slight

Exit turn continues through < 180 degrees

turn continues through < 180 degrees

Sink rate after 720 °[m/s] 7

7

[B-line stall](#)

|1-2

|1-2

Entry easy

easy

Exit spontaneous

spontaneous

| | | |
|--|---|---|
| Big ears | 1-2 | 1-2 |
| | Entry easy Recovery spontaneous, quickly | easy spontaneous, quickly |
| Landing | 1-2 | 1-2 |
| | Landing behaviour easy | easy |
| Front collapse (accelerated) | 2 | 2 |
| | Pre-acceleration average Opening behaviour spontaneous, delayed | average spontaneous, delayed |
| Asymmetric collapse (accelerated) | 2-3 | 2-3 |
| | Turn tendency > 360 degrees Change of course > 360 degrees Rate of turn average with deceleration Max. roll/pitch angle greater than 45 degrees Loss of altitude average Stabilization spontaneous Opening behaviour spontaneous, delayed | > 360 degrees > 360 degrees average with deceleration greater than 45 degrees average spontaneous spontaneous, delayed |
| Big ears accelerated | 1-2 | 1-2 |
| | Entry easy Recovery spontaneous, quickly | easy spontaneous, quickly |

by Jursa Consulting