



DHV-tested Equipment | Flying Equipment Database | Manufacturers / Dealers | Flying Schools | Clubs

DHV Databases

[TECHNICAL DATA](#) [DHV TESTREPORT LTF](#) [DATASHEET](#) [PARTS LIST](#) [PRINT](#)
DHV TEST REPORT LTF 2003**NOVA ROOKIE S****Type designation** Nova Rookie S**Type test reference no** DHV GS-01-1531-06**Holder of certification** NOVA Vertriebsgesellschaft m.b.H.**Manufacturer** NOVA Vertriebsgesellschaft m.b.H.**Classification** 1-2 GH**Winch towing** Yes**Number of seats min / max** 1 / 1**Accelerator** Yes**Trimmers** No

BEHAVIOUR AT MIN WEIGHT IN FLIGHT (75KG)	BEHAVIOUR AT MAX WEIGHT IN FLIGHT (100KG)
---	--

Take off

1

1

Inflation evenly, immediately**Rising behaviour** immediately comes over pilot**Take off speed** average**Take off handling** easy

evenly, immediately

immediately comes over pilot

average

easy

Straight flight

1-2

1-2

Roll damping average

average

Turn handling

1-2

1

Spin tendency slight**Control travel** average**Agility** high

not available

average

average

Symmetric stall

1

1

Deep-stall limit late > 75 cm**Full stall limit** late > 80 cm**Increase in steering power** high

average 60 cm - 75 cm

average 65 cm - 80 cm

average

Front collapse

1-2

1-2

Pre-acceleration average**Opening behaviour** spontaneous, delayed

slight

spontaneous, delayed

Asymmetric collapse

1

1

Turn tendency < 90 degrees**Change of course** < 90 degrees**Rate of turn** average

with deceleration

Max. roll/pitch angle less than 45 degrees**Loss of altitude** average**Stabilization** spontaneous**Opening behaviour** spontaneous

< 90 degrees

90 - 180 degrees

average

with deceleration

less than 45 degrees

slight

spontaneous

spontaneous

Countersteering an asymmetric collapse

1

1-2

Stabilization countersteering easy**Control travel** high**Control pressure increase** high**Turn in opposite direction** easy, no tendency to stall**Opening behaviour** spontaneous, delayed

countersteering easy

average

average

easy, no tendency to stall

spontaneous, delayed

Full stall, symm. exit

1

1

Spin out of straight flight

1-2

1-2

Spin out of turn

1

1

Spiral dive

1-2

1-2

Entry easy**Spin tendency** slight**Exit** spontaneous**Sink rate after 720 °[m/s]** 8

easy

slight

turn continues through < 180 degrees

8

B-line stall

1

1

Entry easy**Exit** spontaneous

easy

spontaneous

Big ears	1	1
	Entry easy	easy
	Recovery spontaneous, quickly	spontaneous, quickly
Landing	1	1
	Landing behaviour easy	easy
Front collapse (accelerated)	1-2	1-2
	Pre-acceleration slight	average
	Opening behaviour spontaneous, delayed	spontaneous, delayed
Asymmetric collapse (accelerated)	1	1-2
	Turn tendency < 90 degrees	90 - 180 degrees
	Change of course 90 - 180 degrees	90 - 180 degrees
	Rate of turn average	average
	with deceleration	with deceleration
	Max. roll/pitch angle less than 45 degrees	less than 45 degrees
	Loss of altitude average	average
	Stabilization spontaneous	spontaneous
	Opening behaviour spontaneous	spontaneous
Big ears accelerated	1	1
	Entry easy	easy
	Recovery spontaneous, quickly	spontaneous, quickly

by Jursa Consulting