



DHV-tested Equipment

Flying Equipment Database

Manufacturers / Dealers

Flying Schools

Clubs

DHV Databases

TECHNICAL DATA

DHV TESTREPORT LTF

DATASHEET

PARTS LIST

PRINT



DHV TEST REPORT LTF 2003

NOVA SYNTAX S

Type designation Nova Syntax S
Type test reference no DHV GS-01-1188-04
Holder of certification [NOVA Vertriebsgesellschaft m.b.H.](#)
Manufacturer [NOVA Vertriebsgesellschaft m.b.H.](#)
Classification 1-2 GH
Winch towing Yes
Number of seats min / max 1 / 1
Accelerator Yes
Trimmers No

	BEHAVIOUR AT MIN WEIGHT IN FLIGHT (75KG)	BEHAVIOUR AT MAX WEIGHT IN FLIGHT (100KG)
Take off	1	1
Inflation	evenly, immediately	evenly, immediately
Rising behaviour	immediately comes over pilot	immediately comes over pilot
Take off speed	average	average
Take off handling	easy	easy
Straight flight	1-2	1-2
Roll damping	average	average
Turn handling	1-2	1-2
Spin tendency	slight	slight
Control travel	average	average
Agility	average	average
Symmetric stall	1-2	1
Deep-stall limit	average 60 cm - 75 cm	average 60 cm - 75 cm
Full stall limit	average 65 cm - 80 cm	average 65 cm - 80 cm
Increase in steering power	average	average
Front collapse	1	1
Pre-acceleration	slight	slight
Opening behaviour	spontaneous, quickly	spontaneous, quickly
Asymmetric collapse	1	1-2
Turn tendency	90 - 180 degrees	90 - 180 degrees
Change of course	90 - 180 degrees	90 - 180 degrees
Rate of turn	slight	average with deceleration
Max. roll/pitch angle	less than 45 degrees	less than 45 degrees
Loss of altitude	slight	slight
Stabilization	spontaneous	spontaneous
Opening behaviour	spontaneous	spontaneous
Countersteering an asymmetric collapse	1-2	1-2
Stabilization	countersteering easy	countersteering easy
Control travel	average	average
Control pressure increase	average	average
Turn in opposite direction	easy, no tendency to stall	easy, no tendency to stall
Opening behaviour	spontaneous, delayed	spontaneous, delayed
Full stall, symm. exit	1-2	1-2
Spin out of straight flight	1-2	1-2
Spin out of turn	1-2	1-2
Spiral dive ⚠	1-2	1
Entry	easy	easy
Spin tendency	slight	slight
Exit	spontaneous	spontaneous
Sink rate after 720 °[m/s]	5	6
B-line stall	1	1
Entry	easy	easy
Exit	spontaneous	spontaneous

Big ears	1	1
Entry easy		easy
Recovery spontaneous, quickly		spontaneous, quickly
Landing	1	1
Landing behaviour easy		easy
Front collapse (accelerated)	1	1-2
Pre-acceleration average		average
Opening behaviour spontaneous, quickly		spontaneous, delayed
Asymmetric collapse (accelerated)	1-2	1-2
Turn tendency 90 - 180 degrees		90 - 180 degrees
Change of course 90 - 180 degrees		90 - 180 degrees
Rate of turn average with deceleration		average with deceleration
Max. roll/pitch angle less than 45 degrees		less than 45 degrees
Loss of altitude slight		slight
Stabilization spontaneous		spontaneous
Opening behaviour spontaneous		spontaneous
Big ears accelerated	1	1
Entry easy		easy
Recovery spontaneous, quickly		spontaneous, quickly