



DHV-tested Equipment

Flying Equipment Database

Manufacturers / Dealers

Flying Schools

Clubs

DHV Databases

TECHNICAL DATA

DHV TESTREPORT LTF

DHV TESTREPORT EN

DATASHEET

PRINT



DHV TESTREPORT EN926-2:2014

NOVA MENTOR 5 S

Type designation NOVA Mentor 5 S
Type test reference no DHV GS-01-2254-16
Holder of certification [NOVA Vertriebsgesellschaft m.b.H.](#)
Manufacturer [NOVA Vertriebsgesellschaft m.b.H.](#)
Classification B
Winch towing No
Number of seats min / max 1 / 1
Accelerator Yes
Trimmers No



BEHAVIOUR AT MIN WEIGHT IN FLIGHT (80KG)

Test pilots



Beni Stocker

BEHAVIOUR AT MAX WEIGHT IN FLIGHT (100KG)



Harald Buntz

Inflation/take-off

Rising behaviour Smooth, easy and constant rising
Special take off technique required No

A

Rising behaviour Smooth, easy and constant rising
Special take off technique required No

Landing

Landing A
Special landing technique required No

A

Landing A
Special landing technique required No

Speeds in straight flight

Trim speed more than 30 km/h Yes
Speed range using the controls larger than 10 km/h Yes
Minimum speed Less than 25 km/h

A

Trim speed more than 30 km/h Yes
Speed range using the controls larger than 10 km/h Yes
Minimum speed Less than 25 km/h

Control movement

Symmetric control pressure Increasing
Symmetric control travel Greater than 60 cm

A

Symmetric control pressure Increasing
Symmetric control travel Greater than 60 cm

Pitch stability exiting accelerated flight

Dive forward angle on exit Dive forward less than 30°
Collapse occurs No

A

Dive forward angle on exit Dive forward less than 30°
Collapse occurs No

Pitch stability operating controls during accelerated flight

Collapse occurs No

A

Collapse occurs No

Roll stability and damping

Oscillations Reducing

A

Oscillations Reducing

Stability in gentle spirals

Tendency to return to straight flight Spontaneous exit

A

Tendency to return to straight flight Spontaneous exit

en : Verhalten beim Verlassen einer vollständigen Steilspirale

en : Erstes Ansprechen des Gleitschirms (die ersten 180°) Drehgeschwindigkeit
Tendency to return to straight flight en : selbstständiges Ausleiten (G-Kraft abnehmend, Drehgeschwindigkeit abnehmend)
Turn angle to recover normal flight Less than 720°, spontaneous recovery

A

en : unmittelbare Verringerung der Drehgeschwindigkeit
en : selbstständiges Ausleiten (G-Kraft abnehmend, Drehgeschwindigkeit abnehmend)
Less than 720°, spontaneous recovery

Symmetric front collapse

B
Entry Rocking back less than 45°
Recovery Spontaneous in 3 s to 5 s

B

Rocking back less than 45°
Spontaneous in 3 s to 5 s

Dive forward angle on exit Dive forward 0° to 30°	Dive forward 0° to 30°
Change of course Entering a turn of less than 90°	Entering a turn of less than 90°
Cascade occurs No	No
en : Faltleinen wurden benutzt no	no
en : Symmetrischer Frontklapper mindestens 50% Flügeltiefe B	B
Entry Rocking back less than 45°	Rocking back less than 45°
Recovery Spontaneous in 3 s to 5 s	Spontaneous in 3 s to 5 s
Dive forward angle on exit Dive forward 30° to 60°	Dive forward 30° to 60°
Change of course Entering a turn of less than 90°	Entering a turn of less than 90°
Cascade occurs No	No
en : Faltleinen wurden benutzt no	no
en : Symmetrischer Frontklapper im beschleunigten Flug B	B
Entry Rocking back less than 45°	Rocking back less than 45°
Recovery Spontaneous in 3 s to 5 s	Spontaneous in 3 s to 5 s
Dive forward angle on exit Dive forward 30° to 60°	Dive forward 30° to 60°
Change of course Entering a turn of less than 90°	Entering a turn of less than 90°
Cascade occurs No	No
en : Faltleinen wurden benutzt no	no
Exiting deep stall (parachutal stall) A	A
Deep stall achieved Yes	Yes
Recovery Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit Dive forward 0° to 30°	Dive forward 0° to 30°
Change of course Changing course less than 45°	Changing course less than 45°
Cascade occurs No	No
High angle of attack recovery A	A
Recovery Spontaneous in less than 3 s	Spontaneous in less than 3 s
Cascade occurs No	No
Recovery from a developed full stall A	A
Dive forward angle on exit Dive forward 0° to 30°	Dive forward 0° to 30°
Collapse No collapse	No collapse
Cascade occurs (other than collapses) No	No
Rocking back Less than 45°	Less than 45°
Line tension Most lines tight	Most lines tight
en : Kleiner einseitiger Klapper A	A
Change of course until re-inflation Less than 90°	Less than 90°
Maximum dive forward or roll angle Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour Spontaneous re-inflation	Spontaneous re-inflation
Total change of course Less than 360°	Less than 360°
Collapse on the opposite side occurs en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)	en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)
Twist occurs No	No
Cascade occurs No	No
en : Faltleinen wurden benutzt no	no
en : Großer einseitiger Klapper B	B
Change of course until re-inflation 90° to 180°	90° to 180°
Maximum dive forward or roll angle Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour Spontaneous re-inflation	Spontaneous re-inflation
Total change of course Less than 360°	Less than 360°
Collapse on the opposite side occurs en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)	en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)
Twist occurs No	No
Cascade occurs No	No
en : Faltleinen wurden benutzt no	no
en : Kleiner einseitiger Klapper im beschleunigten Flug A	A
Change of course until re-inflation Less than 90°	Less than 90°
Maximum dive forward or roll angle Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour Spontaneous re-inflation	Spontaneous re-inflation
Total change of course Less than 360°	Less than 360°
Collapse on the opposite side occurs en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)	en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)
Twist occurs No	No
Cascade occurs No	No
en : Faltleinen wurden benutzt no	no
en : Großer einseitiger Klapper im beschleunigten Flug B	B
Change of course until re-inflation 90° to 180°	90° to 180°
Maximum dive forward or roll angle Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour Spontaneous re-inflation	Spontaneous re-inflation
Total change of course Less than 360°	Less than 360°
Collapse on the opposite side occurs en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)	en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)

	Wiederöffnung)	selbstständiger Wiederöffnung)
Twist occurs	No	No
Cascade occurs	No	No
en : Fatleinen wurden benutzt	no	no
<u>Directional control with a maintained asymmetric collapse</u>	A	A
Able to keep course	Yes	Yes
180° turn away from the collapsed side possible in 10 s	Yes	Yes
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	More than 50 % of the symmetric control travel
<u>Trim speed spin tendency</u>	A	A
Spin occurs	No	No
<u>Low speed spin tendency</u>	A	A
Spin occurs	No	No
<u>Recovery from a developed spin</u>	A	A
Spin rotation angle after release	Stops spinning in less than 90°	Stops spinning in less than 90°
Cascade occurs	No	No
<u>B-line stall</u>	A	A
Change of course before release	Changing course less than 45°	Changing course less than 45°
Behaviour before release	Remains stable with straight span	Remains stable with straight span
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 30° to 60°	Dive forward 30° to 60°
Cascade occurs	No	No
<u>Big ears</u>	B	A
Entry procedure	Dedicated controls	Dedicated controls
Behaviour during big ears	Stable flight	Stable flight
Recovery	Recovery through pilot action in less than a further 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
<u>Big ears in accelerated flight</u>	B	A
Entry procedure	Dedicated controls	Dedicated controls
Behaviour during big ears	Stable flight	Stable flight
Recovery	Recovery through pilot action in less than a further 3 s	Spontaneous in 3 s to 5 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Stable flight
<u>Alternative means of directional control</u>	A	A
180° turn achievable in 20 s	Yes	Yes
Stall or spin occurs	No	No
<u>Any other flight procedure and/or configuration described in the user's manual</u>		
No other flight procedure or configuration described in the user's manual		